

DATA SHEET INSYS MRO-L200

SENSORS AND INTERFACES

Real time Clock	Yes
LAN/Ethernet	Yes
RS 232	Yes
RS 485	No
Digital In	2
Digital Out	1

CONNECTIVITY

4G/LTE	Yes
3G	Yes
GSM	
2G	Yes
GSM connectivity in areas with poor signal	Yes, SMA
Fixed Line Connectivity	Yes (LAN)
Other	No

PROTOCOL LAYER/Framework

Modbus TCP	Optional
Modbus RTU	Optional

PHYSICAL DEVICE CHARACTERISTICS

Maximum Device Size	54 mm x 88 mm x 117 mm
Switchboard Installation	Yes
Operating Temperature	-30 °C/+70 °C (75 °C restricted)
Operating Humidity	0 – 95 %

ELECTRICAL CHARACTERISTICS

Power Supply	12 – 24 V DC
--------------	--------------

CERTIFICATION

CE and WEEE	Yes
FCC	Yes
Other (e. g. other countries, additional certificates)	Optional

CLOUD OF THINGS USE CASE

Alarms will be sent to client	Yes
Self-registration	Yes



CONTACT

Deutsche Telekom AG
Friedrich-Ebert-Allee 140
53113 Bonn
iot-device-support@telekom.de



LIFE IS FOR SHARING.