

# DATA SHEET SITEC S7 TRACKPRO X

## SENSORS AND INTERFACES

Accelerometer	Yes
3D G sensors	Yes
GNSS (GPS)	Yes
Real time Clock	Yes
Temperature Sensor	No
LAN/Ethernet	2
USB	Yes
RS 232	Yes
RS 485	No
I2C Bus	Yes
Digital In	3
Digital Out	3
Analog In	3
CAN	2
LIN Bus	2
1-Wire	Yes
SPI	No
Analog to Digital Converter	No
Audio In/Out	No
SIM-Slot	Mini-SIM or Component-SIM

## CONNECTIVITY

GSM	
2G	No
3G	Yes
LTE	Yes
Fixed Line Connectivity	No
Bluetooth	Yes

## PROTOCOL LAYER/Framework

Ethernet/IP	Yes
CAN Bus	Yes
OPC-UA	Yes

## PHYSICAL DEVICE CHARACTERISTICS

Maximum Device Size	205 mm x 140 mm x 86 mm
Switchboard Installation	No
Maximum IP Class	IP65
Operating Temperature	-40 °C/+75 °C
Storage Temperature	-40 °C/+85 °C

## ELECTRICAL CHARACTERISTICS

Rechargeable battery	No
Power Supply	7 - 42 V DC



LIFE IS FOR SHARING.

# DATA SHEET SITEC S7 TRACKPRO X

## CERTIFICATION

CE	Yes
FCC	No
ECE	No
Lithium Battery CB	No

## CLOUD OF THINGS USE CASE

Self-registration	Yes
Measurement values	Yes
Update device data	Yes
Update device configuration	Yes
Events will be sent to client	No
Alarms will be sent to client	No
Tracking data will be sent to backend	No
Remote Control	No
Firmware over the air updates	Yes



## CONTACT

Deutsche Telekom AG  
Friedrich-Ebert-Allee 140  
53113 Bonn  
[iot-device-support@telekom.de](mailto:iot-device-support@telekom.de)



LIFE IS FOR SHARING.