

Teltonika: RUT240

SENSORS AND INTERFACES

Accelerometer	
3D G sensors	
GNSS (GPS)	
GLONASS (GPS)	
A-GPS	
Real time Clock	
Temperature Sensor	internal
LAN/Ethernet	2x 10/100 Mbps
USB	
RS 232	
RS 485	
NTC	
PT1000	
0...10 V	
4...20 mA	
I2C Bus	
Digital In	1
Digital Out	1
CAN	
LIN Bus	
1-Wire	
SPI	
Analog to Digital Converter	
Audio In/Out	
SIM-Slot	1x2FF
Processor	Atheros Hornet, MIPS 24Kc, 400 MHz
Storage	64 MB DDR2 RAM, 16 MB SPI Flash
Other Interfaces/sensors/comments	

CONNECTIVITY

GSM	Yes
2G	EMEA: B3, B8 LATAM: B2, B3, B5, B8
3G	EMEA: B1, B8 US T-Mobile & ATnT: B2, B4, B5 AU: B1, B5 LATAM: B1, B2, B5, B8 JAPAN: B1, B6, B8, B19
LTE	EMEA: LTE-FDD B1, B3, B7, B8, B20, B28A US T-Mobile & ATnT: LTE- FDD B2, B4, B12 US Verizon: LTE-FDD B4, B13 AU: LTE-FDD B1, B3, B5, B7, B28 LATAM: LTE-FDD B1, B2, B3, B4, B5, B7, B8, B28; LTE-TDD B40 JAPAN: LTE-FDD B1, B3, B8, B18, B19, B26; LTE-TDD B41
GSM connectivity in areas with poor signal	
Fixed Line Connectivity	No
Bluetooth	No
WLAN	802.11b/g/n
Other	

PROTOCOL LAYER/Framework

Ethernet/IP	10/100 Mbps
Modbus TCP	Yes
Modbus RTU	No
CAN Bus	
OPC-UA	
Rockwell	
Siemens Logo	
Siemens S7	
Other	



LIFE IS FOR SHARING.

Teltonika: RUT240

PHYSICAL DEVICE CHARACTERISTICS

Maximum Device Size	83 mm x 74 mm x 25 mm
Switchboard Installation	Yes
DIN Rail mounting	Yes
Maximum IP Class	IP30
Operating Temperature	-40 °C to 75 °C
Storage Temperature	-45 °C to 80 °C
Operating Humidity	10 % to 90 % non-condensing
Storage Humidity	5 % to 95 % non-condensing

ELECTRICAL CHARACTERISTICS

Rechargeable battery	No
Usage with one battery (capacity)	No
Power Supply	9-30 VDC
Other	

CERTIFICATION

CE and WEEE	Yes
E-mark	No
FCC	Yes
ECE	No
IC	Yes
RCM	Yes
RED	Yes
R&TTE	N/A
PTCRB	Yes
Lithium Battery CB	
Other Certificates	EAC, CCC, RoHS, Postel, REACH

CLOUD OF THINGS USE CASE

Dependent on the implemented agent (project specific)	
Self-registration	Yes, initial registration manual
Reboot device	Yes
Measurement values	Yes
Update device data	Yes
Update device configuration	Yes
TLS support	Yes
Connection continuation	Yes
Events will be sent to client	Yes
Alarms will be sent to client	Yes
Tracking data will be sent to backend	
Configuration settings can be changed via CoT	
Remote Control	Yes
Stability Test	Yes
Firmware over the air updates	Yes



CONTACT

Deutsche Telekom AG
 Friedrich-Ebert-Allee 140
 53113 Bonn
iot-device-support-@telekom.de



LIFE IS FOR SHARING.