

# INSYS MICROELECTRONICS GMBH: SCR-L300



## Physical Properties

Programming Interface	Ethernet
Switchboard Installation (DIN rail mounting)	Yes
Device Size	105 × 118 × 42 mm
Weight	270 g
IP Class 1st Digit	4 - Protected against solid objects over 1.0mm e.g. wires.
IP Class 2nd Digit	0 - No protection
Operating Temperature	-30°C / 75°C
Storage Temperature	-30°C / 75°C
Operating Humidity	max. 95%, not condensing
Storage Humidity	max. 95%, not condensing
Number of SIM Slots	1
SIM Type	2FF

## Electrical Characteristics

External Voltage	12 - 24 V DC (+-20%)
------------------	----------------------

## Antennas

GSM Antenna Connector (number)	1
GSM Antenna Connector (standard)	SMA female

## Sensors and IO

RTC	Yes
LAN Ethernet	Yes
RS 232	Yes
Digital In	2
Digital Out	2

## Connectivity

2G	Yes
4G	Yes
Ethernet	Yes

## Supported Protocol Layers / Frameworks

Siemens S7	Optional
Siemens Logo	Optional
Ethernet IP	Yes
Modbus TCP	Yes
Modbus RTU	Yes
OPC-UA	Optional
Other	Optional via icom Data Suite IEC 60870-5-101 master and IEC 60870-5-104 server, Codesys

## System Characteristics

Processor	ARMv7
Storage	3 GB



# INSYS MICROELECTRONICS GMBH: SCR-L300

## Certification

CE	Yes
Directive for Radio Equipment	RED
RoHS	Yes
WEEE	Yes
WEEE valid for	DE

## Cloud of Things

Connectivity with CoT	REST
SmartREST	Yes
SmartREST Prefix	LW-300_19773598

## Safety and Security

TLS	1.2
Encryption mechanisms	AES

### Contact

Deutsche Telekom AG  
Friedrich-Ebert-Allee 140  
53113 Bonn  
[iot-device-support@telekom.de](mailto:iot-device-support@telekom.de)



LIFE IS FOR SHARING