

PSSYSTEM GMBH: SMARTBOX MINI ETH



Physical Properties

Programming Interface	AT commands
Switchboard Installation (DIN rail mounting)	Yes
Device Size	(72 x 53.5 x 26) mm
Weight	89g
IP Class 1st Digit	2 - Protected against solid objects over 12.5mm e.g. hands, large tools.
IP Class 2nd Digit	0 - No protection
Operating Temperature	-20 °C / 60 °C
Storage Temperature	-40 °C / 85 °C
Operating Humidity	max. 85%
Storage Humidity	max. 85%
Number of SIM Slots	1
SIM Type	2FF

Electrical Characteristics

External Voltage	12 - 24 V DC
------------------	--------------

Antennas

GSM Antenna Connector (number)	1
GSM Antenna Connector (standard)	SMA

I/O

RTC	Yes
Number of Ethernet Ports	1
Data transfer rate of Ethernet Port(s)	10/100 Mbps
USB	Yes

Supported Positioning Technologies

GLONASS	Optional
GPS	Optional

Connectivity

2G	Yes
3G	Yes
4G	Optional
NB-IoT	Optional
LTE-M	Optional

Supported Protocol Layers / Frameworks

Modbus TCP	Yes
------------	-----



PSSYSTEMEC GMBH: SMARTBOX MINI ETH

Certification

CE	Yes
Directive for Radio Equipment	RED
RoHS	Yes
WEEE	Yes
WEEE valid for	DE

Cloud of Things

Connectivity with CoT	MQTT
SmartREST	Yes
SmartREST Prefix	_<XID>
Cloud Fieldbus	Yes

Safety and Security

TLS	1.2
Encryption mechanisms	AES

Contact

Deutsche Telekom IoT GmbH
Friedrich-Ebert-Allee 71-77
53113 Bonn
iot-device-support@telekom.de

