

FP INOVOLABS GMBH: FP S-ENGUARD W550 BB



Physical Properties

Programming Interface	TiXML (XML compatible script language)
Device Size	(231 x 158 x 60) mm
Weight	0.66 kg
IP Class 1st Digit	6 - Totally protected against dust ingress.
IP Class 2nd Digit	5 - Protected against water projected by a nozzle (6.3 mm) against enclosure from any direction.
Operating Temperature	min. -25°C, max. 65°C
Storage Temperature	min. -40°C, max. 85°C
Operating Humidity	max. 95 % non-condensing
Storage Humidity	max. 95 % non-condensing
Number of SIM Slots	1
SIM Type	2FF

Electrical Characteristics

External Voltage	110 - 240 V AC
-------------------------	----------------

System Characteristics

Processor	400 MHz, ARM9, ATMEL SAM9-G25
Flash	128 MB on-board
RAM	128 MB DDR2-RAM

Connectivity

2G	Yes
3G	Yes
4G	Yes
Ethernet	Yes
WiFi	Optional

Antennas

GSM Antenna Connector (number)	1
GSM Antenna Connector (standard)	FME (male)



FP INOVOLABS GMBH: FP S-ENGUARD W550 BB

I/O

RTC	Yes
Number of Ethernet Ports	1
Data transfer rate of Ethernet Port(s)	10/100 Mbps
USB	Yes
RS 232	Yes
RS 485	Yes
I2C-Bus	Yes
1-wire	Yes
Digital In	2
Digital Out	1
Others	Up to 3x Pulse inputs for metering systems, 1x M-Bus for energy monitoring for 25 devices

Internal Sensors

Internal Temperature Sensor	DS18B20
-----------------------------	---------

Supported Protocol Layers / Frameworks

Siemens S7	Yes
Siemens Logo	Yes
Modbus TCP	Yes
Modbus RTU	Yes
M-Bus	Yes
Other	ABB, Mitsubishi, Moeller/Eaton, Allen-Bradley, Schneider, Crouzet, VIPA

Certification

CE	Yes
Directive for Radio Equipment	RED
RoHS	Yes
WEEE	Yes
WEEE valid for	DE

Cloud of Things

Connectivity with CoT	MQTT
SmartREST	Yes
SmartREST Prefix	FPIL_TIXIGW_100

Safety and Security

TLS	1.2
Encryption mechanisms	AES

Contact

Deutsche Telekom IoT GmbH
Friedrich-Ebert-Allee 71-77
53113 Bonn
iot-device-support@telekom.de



LIFE IS FOR SHARING